



Basic features

| | |
|------------------------|-----------------------------|
| Approval/Conformity | CE UKCA cULus WEEE |
| Basic standard | IEC 60947-5-2 |
| Principle of operation | Inductive sensor |
| Trademark | Proxinox® |

Display/Operation

| | |
|--------------------|-----|
| Function indicator | yes |
| Power indicator | no |

Electrical connection

| | |
|-----------------------------------|----------------------------|
| Connection | M12x1-Male, 4-pin, A-coded |
| Polarity reversal protected | yes |
| Protection against device mix-ups | yes |
| Short-circuit protection | yes |

Electrical data

| | |
|-----------------------------------|-------------|
| Load capacitance max. at Ue | 0.5 µF |
| Min. operating current Im | 0 mA |
| No-load current Io max., damped | 10 mA |
| No-load current Io max., undamped | 3 mA |
| Operating voltage Ub | 10...30 VDC |
| Output resistance Ra | 33.0 kOhm |
| Rated insulation voltage Ui | 75 V DC |
| Rated operating current Ie | 200 mA |
| Rated operating voltage Ue DC | 24 V |
| Rated short circuit current | 100 A |
| Ready delay tv max. | 15 ms |
| Residual current Ir max. | 50 µA |
| Ripple max. (% of Ue) | 15 % |
| Switching frequency | 2000 Hz |
| Utilization category | DC -13 |
| Voltage drop static max. | 2 V |

Environmental conditions

| | |
|-------------------------|--|
| Ambient temperature | -25...85 °C |
| Chemical resistance | 6 % H2O2 solution 15 % H2O2 solution 3 % H2O2 solution |
| Contamination scale | 3 |
| EN 60068-2-27, Shock | Half-sinus, 30 gn, 11 ms |
| EN 60068-2-6, Vibration | 55 Hz, amplitude 1 mm, 3x30 min |
| IP rating | IP68, according to BWN Pr 20 |
| IP rating per DIN 40050 | IP69K |

Functional safety

| | |
|--------------|-------|
| MTTF (40 °C) | 830 a |
|--------------|-------|

Interface

Switching output PNP normally open (NO)

Material

Housing material 1.4404 stainless steel
 Material sensing surface LCP

Mechanical data

Dimension \varnothing 12 x 45 mm
 Installation for flush mounting
 Mounting length 30.00 mm
 Size M12x1
 Tightening torque 12 Nm

Range/Distance

Assured operating distance Sa 3.2 mm
 Hysteresis H max. (% of Sr) 15.0 %
 Rated operating distance Sn 4 mm
 Real switching distance sr 4 mm
 Repeat accuracy max. (% of Sr) 5.0 %
 Switching distance marking ■■
 Temperature drift max. (% of Sr) 10 %
 Tolerance Sr \pm 10 %

Remarks

The sensor is functional again after the overload has been eliminated.
 For more information about MTTF and B10d see MTTF / B10d Certificate

Indication of the MTTF- / B10d value does not represent a binding composition and/or life expectancy assurance; these are simply experiential values with no warranty implications. These declared values also do not extend the expiration period for defect claims or affect it in any way.

Connector Drawings



Wiring Diagrams (Schematic)

